Volume 2674

Proceedings of 7th International Conference on Industrial, Mechanical, Electrical and Chemical Engineering 2021 (ICIMECE 2021)

Surakarta, Indonesia • 5 October 2021

Editors • Mujtahid Kaavessina, Anatta Wahyu Budiman, Muhammad Hamka Ibrahim, Muhammad Hisjam, Aditya Rio Prabowo, Endah Retno Dyartanti and Subuh Pramono





Issues

Select Decade 2020 V Select Year 2023 V Issue 12 May - Volume 2674, Issue 1
PRELIMINARY
Preface: International Conference on Industrial, Mechanical, Electrical and Chemical Engineering 2021 (ICIMECE 2021) AIP Conference Proceedings 2674, 010001 (2023) doi: https://doi.org/10.1063/12.0013124 View article Description:
INVITED PAPER
Emerging post-lithium batteries: Opportunities in Indonesia Muhammad Hilmy Alfaruqi AIP Conference Proceedings 2674, 020001 (2023) doi: https://doi.org/10.1063/6.0133085 Abstract V View article
CONTRIBUTED ORAL PAPER
Modeling of a pellet biomass furnace of 200 kW Tito Gusti Nurrohim; Suyitno; Rizqi Abdul Rahman; Heru Sutanto; Mohamad Muqoffa AIP Conference Proceedings 2674, 030001 (2023) doi: https://doi.org/10.1063/5.0124573 Abstract V View article
Lithium-ion cylinder battery power cooling: A review Zeluyvenca Avista; Ubaidillah; Indri Yaningsih; Aditya Rio Prabowo AIP Conference Proceedings 2674, 030002 (2023) doi: https://doi.org/10.1063/5.0117607 Abstract View article PDF
Automation and monitoring system of drying parameters in cabinet dryer using Arduino (temperature and humidity) Ari Rahayuningtyas; Diang Sagita; Novita Dwi Susanti AIP Conference Proceedings 2674, 030003 (2023) doi: https://doi.org/10.1063/5.0114374 Abstract V View article
Preliminary experiment of Saccharomyces cerevisiae immobilization using method of in situ flocculation Aswandi Asmadi; Mujtahid Kaavessina; Margono AIP Conference Proceedings 2674, 030004 (2023) doi: https://doi.org/10.1063/5.0115647 Abstract V View article
Effect of injection molding processing parameters on tensile properties of recycled polypropylene based composites reinforced with bamboo fibers Govinda; Indah Widiastuti AIP Conference Proceedings 2674, 030005 (2023) doi: https://doi.org/10.1063/5.0114104 Abstract V View article
Effect of bamboo fiber alkalization treatment on water sorption characteristics and mechanical properties of recycled polypropylene-bamboo composites Mohammad Khoirul Huda; Indah Widiastuti AIP Conference Proceedings 2674, 030006 (2023) doi: https://doi.org/10.1063/5.0114094 Abstract V View article
Review: Recent developments in the design and application of magnetorheological fluids in the medical field Agus Lutanto; Ubaidillah; Aditya Rio Prabowo; Fitrian Imaduddin; Dimas Adiputra AIP Conference Proceedings 2674, 030007 (2023) doi: https://doi.org/10.1063/5.0117624 Abstract V View article
Preliminary design for manufacturing and assembling bread dough mixer machine Catur Harsito; Anugrah Akbar; Ari Prasetyo; Teguh Triyono; Budi Santoso AIP Conference Proceedings 2674, 030008 (2023) doi: https://doi.org/10.1063/5.0114137

The effect of health warning labels on intention to repurchase cigarettes in Surakarta city using structural equation model method Bagus Muchlis Putra: Lobes Herdiman: Susv Sumartini: Taufig Rochman AIP Conference Proceedings 2674, 030009 (2023) doi: https://doi.org/10.1063/5.0129665 View article PDF Access point configuration on Internet of Things with bootstrap WiFi networking Raspberry Pi Yustina Tritularsih; Hoedi Prasetyo; Fenty Pandansari AIP Conference Proceedings 2674, 030010 (2023) doi: https://doi.org/10.1063/5.0118880 Abstract ∨ View article PDF Regional innovation driving factors model (Cianjur Regency) Anita Ilmaniati; Isma Masrofal AIP Conference Proceedings 2674, 030011 (2023) doi: https://doi.org/10.1063/5.0123398 PDF Integration AHP and MOORA for sustainable supplier selection during the COVID-19 pandemic era: A case study Muhammad Faisal Ibrahim; Tara Laurensia; Dana Marsetiya Utama AIP Conference Proceedings 2674, 030012 (2023) doi: https://doi.org/10.1063/5.0114216 Abstract ✓ View article 🛚 PDF The effect of quenching agents at T6 heat treatment on hardness Al6061-sea sand composite Hafidh Rawi Mufti: Hammar Ilham Akbar: Eko Suroio; Wibowo: Teguh Trivono; Sukmaii Indro Cahvono; Nurul Muhayat; Trivono AIP Conference Proceedings 2674, 030013 (2023) doi: https://doi.org/10.1063/5.0117022 Abstract ✓ View article PDF Assistive technology on the SS1-V1 weapon stock to support shooting stability for DEPOHAR 50 - TNI AU Langgeng Andy Setiawan; Susy Susmartini; Lobes Herdimar AIP Conference Proceedings 2674, 030014 (2023) doi: https://doi.org/10.1063/5.0117357 Abstract ∨ View article PDF Li-ion batteries as energy storage for solar power plant Muhammad Nur Ikhsanudin; Maudy Pratiwi Novia Matovanni; Rizky Ibnufaatih Arvianto; Sunu Herwi Pranolo; Agus Purwanto; Joko Waluyo AIP Conference Proceedings 2674, 030015 (2023) doi: https://doi.org/10.1063/5.0133079 PDF Comparison of the production of dimethyl ether (DME) from lignite coal and biomass as energy sources to substitute LPG: A case study in Indonesia Rizky Ibnufaatih Arvianto; Muhammad Nur Ikhsanudin; Maudy Pratiwi Novia Matovanni; Anatta Wahyu Budiman; Sunu Herwi Pranolo; Joko AIP Conference Proceedings 2674, 030016 (2023) doi: https://doi.org/10.1063/5.0114394 PDF The thermophysical properties, configurations and applications of nanofluids on solar PV/T system: A review Nuha Khairunnisa: Zainal Arifin: Budi Kristiawan: Mohd Afzanizam Mohd Rosli AIP Conference Proceedings 2674, 030017 (2023) doi: https://doi.org/10.1063/5.0114164 Abstract ∨ View article 🖪 PDF The gravitational water vortex turbine: A review and application development Rieky Handoko; Syamsul Hadi; D. Danardono Dwi P.T.; Ari Prasetyo AIP Conference Proceedings 2674, 030018 (2023) doi: https://doi.org/10.1063/5.0116535 PDF Abstract ∨ View article Selection of materials for the prosthetic liner using coconut water composite as a substitute for EVA Arung Sasmaya Bahari; R. Hari Setyanto; Lobes Herdiman AIP Conference Proceedings 2674, 030019 (2023) doi: https://doi.org/10.1063/5.0114667 View article 🔁 PDF Characteristic of the UAV structural design and platform in military-use environment: State and development Annas Isman Saputro; Aditya Rio Prabowo; D. Danardono Dwi Prija Tjahjana; Ristiyanto Adiputra; Hari Nubli AIP Conference Proceedings 2674, 030020 (2023) doi: https://doi.org/10.1063/5.0117021 Abstract ∨ View article 🔁 PDF

Multicriteria optimization of 3D printed flow restrictor using Taguchi method and PCR-TOPSIS for dimensional accuracy and printing duration Virsha Alviasha; Joko Triyono; Eko Pujianto AIP Conference Proceedings 2674, 030021 (2023) doi: https://doi.org/10.1063/5.0115433 Abstract ∨ View article ₽ PDF Manufacturing green hybrid new material made from bagasse, rice husk ash and reinforced glutinous glue as noise absorption Lobes Herdiman; R. Hari Setyanto; Susy Susmartini; Taufiq Rohman AIP Conference Proceedings 2674, 030022 (2023) doi: https://doi.org/10.1063/5.0116995 🔁 PDF Power efficiency analysis by using UBEC for prosthetic hand 8 Agung Dwicahyo: Lobes Herdiman: Susy Susmartini AIP Conference Proceedings 2674, 030023 (2023) doi: https://doi.org/10.1063/5.0117185 Abstract ✓ View article 🔁 PDF Implementation of lean six sigma reducing E-DOWNTIME waste proposed improvement of flooring board production at PT. LBB Rut Yolanda Karfisa Br Lumbanraja; Fakhrina Fahm; Eko Pujiyanto AIP Conference Proceedings 2674, 030024 (2023) doi: https://doi.org/10.1063/5.0116342 PDF Abstract ∨ View article Formulating strategic purchasing strategy: A case study Hery Suliantoro; Drajat A. Dilaga; M. Mujiya Ulkhaq AIP Conference Proceedings 2674, 030025 (2023) doi: https://doi.org/10.1063/5.0114089 Abstract ✓ View article 🔁 PDF Implementation of fluid-structure interaction (FSI) in marine design: Calculation review on hull structures Rizky Adhi Febrianto; Syamsul Hadi; Raymundus Lulus L. G. Hidayat; Dong Myung Bae; Bo Cao; Aditya Rio Prabowo AIP Conference Proceedings 2674, 030026 (2023) doi: https://doi.org/10.1063/5.0114201 View article Synthesis of superabsorbent (hydrogel) based on banana peel cellulose-acrylamide-carrageenan with microwave Sperisa Distantina; Ivan Satritama; Verania Arneta Putri; Ghea Safiraventa Anggreini AIP Conference Proceedings 2674, 030027 (2023) doi: https://doi.org/10.1063/5.0129655 Abstract ∨ View article 🔁 PDF Rice husks and bagasse as composite materials characterized by heat resistance Larasati Sekar Palupi; Susy Susmartini; R Hari Setyanto AIP Conference Proceedings 2674, 030028 (2023) doi: https://doi.org/10.1063/5.0118261 Abstract ∨ View article PDF Development of ceramic jewellery industry in the form of necklaces with Indonesian batik motifs T. Yuniarto; P. W. Anggoro; B. Bawono; P. K. Fergiawan; A. P. Bayuseno; J. Jamari AIP Conference Proceedings 2674, 030029 (2023) doi: https://doi.org/10.1063/5.0114917 Failure analysis: Hardness and stress study of failed IC engine rocker arms Aprianur Fajri; Nurul Muhayat; Aditya Rio Prabowo; Fitrian Imaduddin; D. Danardono Dwi Prija T.; Ari Prasetyo; Yemi Kuswardi; Jung Min Sohn; Dharu Feby Smaradhana AIP Conference Proceedings 2674, 030030 (2023) doi: https://doi.org/10.1063/5.0117567 Abstract ✓ View article 🛚 PDF A critical review on structural testing and assessment of lightweight sandwich structure for ship structure application Tuswan Tuswan; Abdi Ismail; Achmad Zubaydi; Bambang Piscesa; Nadya Paramita Langening Sukma Sukma AIP Conference Proceedings 2674, 030031 (2023) doi: https://doi.org/10.1063/5.0116355 Abstract ✓ View article 🖪 PDF

Assessment of debonding failures in the sandwich plate of stern ramp door of ferry Ro-Ro using k-nearest neighbor algorithm

Abstract ✓	View article	¹ PDF	
sland .			evaluation of COVID-19 vessel for public health service in Indonesia's remo
Hakim; Good Rin	do; Aditya Rio Pra	abowo; Tegu	dianto; Mahendra Guna Satriananta; Rayhan Satria Dwinata; Abdi Ismail; Muhammad Luqma h Putranto ttps://doi.org/10.1063/5.0115436
Abstract ✓	View article	¹ PDF	
Sari Murni)	k aids on temp		age stations based on Karakuri Kaizen principles (case study: Industri Tah
Abstract ✓	View article	₿ PDF	
Warehouse de	esign under cla	ass-based	storage policy based on entry-item-quantity analysis: A case study
			hammad Faisal Ibrahim Itps://doi.org/10.1063/5.0114493
Abstract >	View article	₽ PDF	
Abstract	view article	E POP	
	-		ssava bagasse-acrylamide-carrageenan bead gel
			as Rizqi Damarjati Listyono; Nurul Hidayatun ttps://doi.org/10.1063/5.0129645
Abstract ∨	View article	₽ PDF	
Samuel; Aji Setia	wan; Eko Sasmito	Hadi; Muha	ation on patrol boat ammad lqbal; Parlindungan Manik ttps://doi.org/10.1063/5.0114759
Abstract ✓	View article	₽ PDF	
	B. Kristiawan; Su		Juwana; R. A. Rachmanto; C. H. Brillianto; S. D. Prasetyo; A. F. Muhammad; Z. Arifin ttps://doi.org/10.1063/5.0114153
Abstract ✓	View article	₽ PDF	
magnetics (FE	EMM)		ogical fluids (MRFs) simulation studies with finite element methods for
			ttps://doi.org/10.1063/5.0119051
Abstract ✓	View article	2 PDF	
Haris Nubli; Jung	Min Sohn	·	et-fire release on LNG bunkering vessel
AIP Conference Prod	ceedings 2674, 03004	0 (2023) doi: h	ltps://doi.org/10.1063/5.0117438
Abstract ∨	View article	¹ PDF	
Hanifah Yulia; Su	buh Pramono; Su	trisno; B. D.	
	_		ttps://doi.org/10.1063/5.0114101
Abstract ∨	View article	₽ PDF	
			ssification and territory status review Tjahajana; Aditya Rio Prabowo; Ristiyanto Adiputra
AIP Conference Prod	ceedings 2674, 03004	2 (2023) doi: h	ttps://doi.org/10.1063/5.0129598
Abstract ✓	View article	₽ PDF	
	•		nd swing angle control system on a gantry crane
AIP Conference Prod	ceedings 2674, 03004	3 (2023) doi: h	ttps://doi.org/10.1063/5.0114501

Identification of design requirements for noodles untangling and cutting machines on non-wheat noodle production line: A QFD approach Novrinaldi; A. Haryanto; U. Hanifah; M. A. Karim; S. A. Putra; E. K. Pramono; A. Sitorus; N. K. I. Mayasti AIP Conference Proceedings 2674, 030044 (2023) doi: https://doi.org/10.1063/5.0114410 Abstract ✓ View article PDF Measuring user experience of a decision support system for operating room scheduling using the user experience questionnaire Pasca Purwoko; Yusuf Priyandari; Cucuk Nur Rosyidi AIP Conference Proceedings 2674, 030045 (2023) doi: https://doi.org/10.1063/5.0114991 PDF Abstract ✓ View article Mathematical modeling of fluidized bed drying kinetics of unhulled rice in a swirling fluidized bed dryer with bed ratio AIP Conference Proceedings 2674, 030046 (2023) doi: https://doi.org/10.1063/5.0114385 View article 🔁 PDF The effect of adding heatsink cooling with concentrator on increasing photovoltaic performance Z. Arifin; M. L. Baharuddin; W. E. Juwana; Suyitno; D. D. D. P. Tjahjana; M. Muqoffa; S. D. Prasetyo AIP Conference Proceedings 2674, 030047 (2023) doi: https://doi.org/10.1063/5.0114139 View article 🔁 PDF Effect of addition of emulsifier Tween 20 on microencapsulation rice bran oil using natural polymers kappacarrageenan and chitosan Fadilah: Ari Diana Susanti: Sperisa Distantina: Viona Rohmah Armia Gita Kusuma: Gemilang Ramadhan Syahputraningrat AIP Conference Proceedings 2674, 030048 (2023) doi: https://doi.org/10.1063/5.0114822 PDF Abstract ✓ View article Low-density parity-check codes (LDPC) 5G -new radio (NR) performance using modified min-sum decoding algorithm Eni Wardihani; Syrico A. Setyawan; Muhammad Mukhlisin AIP Conference Proceedings 2674, 030049 (2023) doi: https://doi.org/10.1063/5.0129761 View article PDF Analysis of gear fault based on acoustic signal and least square support vector machine Didik Djoko Susilo; Achmad Widodo; Toni Prahasto; Muhammad Nizam AIP Conference Proceedings 2674, 030050 (2023) doi: https://doi.org/10.1063/5.0117472 PDF Natural weathering on recycled polypropylene-bamboo fiber composites Arianti Ramadhani: Indah Widiastuti AIP Conference Proceedings 2674, 030051 (2023) doi: https://doi.org/10.1063/5.0118916 Abstract ✓ View article PDF Low cost three-phase electrical power quality analyzer system using PC-based USB DAQ Latif Nur Fauzi; Muhammad Hamka Ibrahim; Muhammad Nizam AIP Conference Proceedings 2674, 030052 (2023) doi: https://doi.org/10.1063/5.0115104 Abstract ∨ View article PDF The optimization of polytetrafluoroethylene (PTFE) cutting parameters for minimizing energy consumption in CNC turning of using Taguchi method Suwondo Adi Saputro; Cucuk Nur Rosyidi; Eko Pujiyanto AIP Conference Proceedings 2674, 030053 (2023) doi: https://doi.org/10.1063/5.0115439 🔁 PDF The effect of volume, ball diameter, and milling time through the ball mill process of corncob Rusdi Nur; Ahmad Nurul Muttaqin; Baso Nasrullah; Dermawan AIP Conference Proceedings 2674, 030054 (2023) doi: https://doi.org/10.1063/5.0116172 Abstract ✓ View article 🔁 PDF

Design and analysis of ozone monitoring system produced by plasma corona discharge for disinfectant Ivan Robi Septian; Miftahul Anwar; M. Maulana Yusuf; Riski Rama Kusuma; Teguh Endah Saraswati; Meiyanto Eko Sulistyo; Feri Adriyanto; Fandi Surya Adinata

	//iew article ☐ ☐ PDF ☐ mixing on electrocoagulation performance during soy sauce wastewater treatment
	P Aryanti; A. A. Dania; F. F. Sari
	ings 2674, 030079 (2023) doi: https://doi.org/10.1063/5.0114686
Abstract ✓	/iew article
Multi-response surface metho	ptimization in injection molding process of PLA bone screw using Taguchi method and respon logy
Rizca Tri Wulanda	Joko Triyono; Eko Pujiyanto
AIP Conference Prod	ings 2674, 030080 (2023) doi: https://doi.org/10.1063/5.0116344
	/iew article

Warehouse design under class-based storage policy based on entry-item-quantity analysis: A case study

Sekarsari Utami Wijaya ➡; Rahayu Johanna; , Muhammad Faisal Ibrahim



AIP Conference Proceedings 2674, 030035 (2023)

https://doi.org/10.1063/5.0114493





CrossMark

Articles You May Be Interested In

Data warehousing in the business intelligence

AIP Conference Proceedings (September 2022)

Real-time data integration in smart warehouse as a contemporary approach

AIP Conference Proceedings (April 2023)

Warehouse layout design with class-based storage approach to minimize material transfer distance

AIP Conference Proceedings (February 2023)





Warehouse Design under Class-Based Storage Policy Based on Entry-Item-Quantity Analysis: A Case Study

Sekarsari Utami Wijaya^{a)}, Rahayu Johanna^{b)}, Muhammad Faisal Ibrahim^{c)}

Department of Logistics Engineering, Universitas Internasional Semen Indonesia, Gresik, Indonesia

a) Corresponding author: sekarsari.wijaya@uisi.ac.id
b) rahayu.johanna17@student.uisi.ac.id
c) muhammad.ibrahim@uisi.ac.id

Abstract. In an effort to minimize the impact of unpredictable demand, the company will make an inventory policy. The warehouse as a place for storing goods before being distributed to consumers has an essential role in ensuring supply sustainability in the supply chain system. Many problems occur in the warehouse which causes a decrease in warehouse performance which has an impact on the company's operations. One of the things that play an essential role in increasing the efficiency of warehouse operations is the warehouse layout design. Class-based storage policies are used to regulate the procedures for storing goods into 3 classifications. Classification is obtained based on Pareto's law by considering the level of storage and retrieval activity. Entry-Item-Quantity (EIQ) analysis is an analysis that involves three main factors of logistics distribution, namely, E (Order Entry), I (Item), and Q (Quantity) which is applied to further analyze frequently ordered products, so that it can support the layout warehouse. UD. XYZ is a distributor that sells many kinds of materials for roofs. This study considers determining the number of racks needed by Entry Item Quantity-Class Based Storage analysis. Furthermore, this study will compare the warehouse layout based on IK, IQ, EN, and EQ. It aims to obtain the best improvement in the warehouse layout that has the smallest expected distance. Based on the analysis that has been done, the warehouse shall provide 14 type 1 racks and 13 type 2 racks. The smallest expected distance, the best warehouse layout design. IQ analysis results in the best warehouse layout design.

Keywords: Class-Based Storage analysis, EIQ analysis, EQ analysis, warehouse.

INTRODUCTION

In practice, every trade tends to have a whole uncertainty about demand. It has encouraged the traders to make policies about the inventory system. Its aims to anticipated unpredictable demand. The policy about inventory systems prompts traders to provide a facility that will be used for a warehouse for storing goods. A warehouse is a facility used as a temporary storage place for goods before being distributed to end consumers. These goods can be raw materials, work in process, and or finished goods. Warehouses play an important role in maintaining the suitability of supply to demand in the supply chain system [1]. Some of the problems that often occur in warehouses include difficulty in moving goods, accumulation of goods, long searching for goods, and lack of capacity. Moving goods that spend a lot of time causing high costs in material handling. Delays occur due to the length of time it takes to search for items. In addition, the pile of goods that are too high makes it difficult to withdraw goods. Warehouse layout is one of the things that affect the efficiency and effectiveness of the warehouse. The appropriate warehouse layout design will play a role in increasing operating efficiency [2].

Class-based storage policies are usually used to regulate goods storage procedures that divide goods into three classes, namely classes A, B, and C [3]. Its classifications are based on the law of Pareto by considering storage and retrieval (S/R) activity rate. This method produces a layout design for the storage area of all kinds of goods based on

their class. Racks are designed to increase storage capacity, the displacement of workers, and retrieval system goods. It is also designed to minimize the distance traveled workers as possible.

Entry-Item-Quantity (EIQ) analysis is applied to further analyze frequently ordered products, so that it can support the distribution center layout. According to [4], EIQ is an analysis involving three main logistics distribution factors namely, E (Order Entry), I (Item), and Q (Quantity). This analysis proposes the improvement of warehouse layout design based on IK (items by order number) is the order frequency of product items purchased by the seller. IQ (Item Quantity) is the number of each kind of goods ordered and purchased by the seller. EN (Entry Quantity) is the number of items purchased by the customer. EQ (Entry Quantity) is the order quantity of customer [5]. EIQ can determine the amount of the rack used in the improved layout of the warehouse by Class-Based Storage.

Previous research about Class-Based Storage with Entry Item Quantity Analysis was conducted by [6]. The differences between previous research and this research is the design of racks. On previous research, a type 1 rack was designed consisting of 2 the level. First level was to utilize pallet wheeled furnished with a brace or lock the wheels and second level used steel as material for making store shelves. Whereas, this experimental design a rack type 1 designed consisting of 2 levels. All of levels use steel materials for making store shelves. Another research that used Class-Based Storage with Entry Item Quantity Analysis is[4]. This difference between two research studies is characteristic goods. According to research by [4], characteristic goods were cigarettes that are distributed to local distributors. Whereas, characteristic goods of this paper is materials for roofs. So, the novelty of this article is about the design of rancks and characteristics of goods.

UD. XZY is a distributor that sells many kinds of materials for roofs. The materials are consist of roofs, tin roof, asbestos roof, roof ridge cap, galvalume roof, and spandex roof. Several problems that were already described had also occurred in this distributor. This study considers determining the number of racks needed by Entry-Item Quantity-Class Based Storage analysis. Furthermore, this study will compare the warehouse layout based on IK, IQ, EN, and EQ. It aims to obtain the best improvement in the warehouse layout that has the smallest expected distance for UD. XYZ.

METHODS

In general, there are five steps to determine the number of racks and the best layout of the warehouse. First, classify goods using the Class-Based Storage method based on IK, IQ, EN, and EQ. The threshold for determining the ABC split is close to 20%, 30%, and 50% of the cumulative percentage of goods ordered. Calculation of the Class-Based Storage as follows: sort the data IK/IQ/EN/EQ from largest to smallest, calculate the cumulative frequency of data IK/IQ/EN/EQ, calculate the percentage of cumulative frequency, and classify the type of goods into A, B, or C class based on threshold determined before. Second, design shelving storage racks. Design storage racks are depended on the heavy and dimensions of goods, the high and wide of the level. Third, calculate the number of racks as storage. Racks are used to store the equipment in the warehouse. This study uses two types of racks, namely, type 1 racks and type 2 racks.

Figure 1 shown the type 1 racks; the rack is used to store roof and roof ridge cap. Type 2 racks are used to store tin roof, asbestos roof, galvalume roof, and spandex roof, shown in Figure 2. To determine how many racks are needed, it can be obtained by calculating the average of recorded stock of goods each day. Then, divide the average of the recorded stock each day by rack capacity.



FIGURE 1. Type 1 Racks




FIGURE 2. Type 2 Racks

Fourth, design warehouse layout by racking systems. Design layout warehouse is adapted to reflect the shelf space defined in the previous step. Last, calculate the expected distance. According to [7], expected distance is the distance that is expected from storage to entry points and freight out of goods. The expected distance for the entire picking path can be calculated by first finding the probability of entering a node and multiplying it by the probability of each arc going out of the node and the distance along the arc [7]. Distance calculation uses Euclidean Distance. The formula is as follow:

$$d_{ij} = \sqrt{(x_i - x_j)^2 + (y_i - y_j)^2}$$
 (1)

where

 $x_i = x$ coordinate of the *i*-th center of facility

 $x_i = x$ coordinate of the *j*-th center of facility

 $y_i = y$ coordinate of the *i*-th center of facility

 $y_i = y$ coordinate of the *j*-th center of facility

 d_{ii} = distance between the *i*-th and *j*-th center of facility

The best warehouse layout design between IK, IQ, EN, and EQ has a minimum expected distance value.

RESULTS AND DISCUSSION

The total size of UD. XYZ warehouse about 260 m². Its length is about 20 m² and its width about 13 m². Only 110 m² of total warehouse size is used to store the materials. The existing warehouse layout design shown in Figure 3 does not consider the distance between the aisle in every location of materials.




FIGURE 3. The Existing Warehouse Layout UD. XYZ

The IK, IQ, EN, EQ, and stock of materials data are collected. Data is collected for six months (November 2020 until April 2021). The four alternative EIQ (IK, IQ, EN, EQ) data is used to classify the Class-Based Storage method. Table 1 shows the result of EIQ data processing approached Class-Based Storage method. The number of materials ordered in class A is the smallest because the proportion of class A about 1% - 20% of accumulated percentage. The highest number of material ordered is in class C because the proportion of class C about the smallest 50% - 100% of accumulated percentage. Class A materials shall be stored in racks near from access door, class B materials shall be stored in racks between class A and class C, and class C materials shall be stored in the common racks due to weak flexibility. This result is suitable as study conducted by [5], the storage position for goods provided for small retailers

shall be arraged in accordance with the result of the ABC classification. Class A products (1% - 20% of accumulated item percentage) shall be stored in the automatic stereoscopic shelves owing to high values and strong flexibility, class C products (20% - 50% of accumulated item percentage) shall be stored in the common shelves due to weak flexibility, and class B products (50% - 100% of accumulated item percentage) shall be jointly stored in the automatic stereoscopic shelves with class A product.

TABLE 1. The Result of Classification EIQ Calculated by Class Based Stroge Method

Classi-	IK		IQ		EN		EQ	
fication	Quantity	Category	Quantity	Category	Quantity	Category	Quantity	Category
A-class	109	7	244.500	6	95	7	102.057	6
B-class	166	12	417.600	13	142	12	158.573	12
C-class	288	30	645.871	30	228	30	272.241	31
Total	554	48	1.307.971	49	465	49	532.871	49

The materials in the warehouse will be stored in racks based on the Class-Based Storage method. The stock of materials is used to determine the number of racks. According to the IK and EN calculation, the warehouse shall provide 14 type 1 racks and 16 type 2 racks. The area is needed about 49,88 m². Meanwhile according to the IQ and EQ calculation, the warehouse shall provide 14 type 1 racks and 13 type 2 racks. The area is needed about 45,46 m². the total area of UD. XYZ about 260 m² (**Table 2**). The area owned UD. XYZ can provide the area required.

TABLE 2. The Number of Racks and Spaces Needed

Type of Rack	Materials	The Number of Levels	The Height between Levels (m)	Capacity (unit)	The Number of Racks	The Dimensions (m²)	The Space Needed (m ²)
			IK and EN	Analysis			, ,
Type 1	Roof and roof ridge cap	2	1	450	14	1x1=1	14
Type 2	Tin roof, asbestos roof, galvalume roof, and spandex roof	3	0,5	100	16	2,2 x 1,1= 2,42	38,72
		Total			30	49,88	3
			IQ and EQ	Analysis			
Type 1	Roof and roof ridge cap	2	1	450	14	1x1=1	14
Type 2	Tin roof, asbestos roof, galvalume roof, and spandex roof	3	0,5	100	13	2,2x1,1=2,42	31,46
		Total			30	45,40	5


According to EIQ analysis, four warehouse layout designs are proposed based on IK, IQ, EN, and IQ. The racks are laid under the quantities required. The materials are also stored in accordance with the result of EIQ-Class-Based Storage analysis (Fig. 4).

The in and out materials data are used for performing calculations on the probability expected distance. Expected distances are calculated by multiplicating the probability of the materials movement from rack to access door and the total distance of the materials movement from rack to access door. Expected distance conducted adapted to the layout of already made from the analysis entry items quantity. So, there is four value of expected distance (**Table 3**). The in and out total distances are same because there is only one access door to in and out the materials. The highest expected distance, the worst warehouse layout design. EN analysis result the worst warehouse layout design because the total

expected distance is about 138,32. The smallest expected distance, the best warehouse layout design. EQ analysis results in the best warehouse layout design. The nearest expected distance can affect the time for material handling. The material handling in IQ's layout design is more effective than others ad also it can affect the costs. It's cost will be more efficient than others. So that, the warehouse layout design proposed to UD. XYZ is the IQ analysis warehouse layout design.

TABLE 3. The Expected Distance

EIQ Analysis	The In Distance (in meter)	The Out Distance (in meter)	Total Expected Distance (in meter)	
Existing	196,01	196,01	196,01	
IK	174,96	174,96	174,96	
IQ	138,32	138,32	138,32	
EN	175,84	175,84	175,84	
EQ	143,92	143,92	143,92	



CONCLUSIONS

FIGURE 4. The Warehouse Layout Design

Warehouse storage is an essential step in the logistics process, which directly reflects the status of the material before and in circulation and serves as the basis for the company in evaluating the materials' production and sales. Based on the analysis that has been done, the warehouse shall provide 14 type 1 racks and 13 type 2 racks. The smallest expected distance, the best warehouse layout design. IQ analysis results in the best warehouse layout design. So that, the warehouse layout design proposed to UD. XYZ is the IQ analysis warehouse layout design.

The weakness of this research is the racks only have two levels on type 1 racks and three levels on type 2 racks. Recommendations for the further research are examining what happens if the type 1 racks can be broken up into three or more partitions and the type 2 racks broken up into four or more partitions with the stonger material of racks to improve the distance estimate and increase the capacity of warehouse. Finally, the next research also try to build a simulation model to gain more insights and validate the expected distance calculations.

ACKNOWLEDGMENTS

This work partially supported by Universitas Internasional Semen Indonesia, especially lecturer in Logistics Engineeering Department. The authors also wish to thank the reviewers for their very constructive comments and suggestions which have helped improve the presentation of the paper.

REFERENCES

- [1] R. B. M. De Koster, A. L. Johnson, and D. Roy, "Warehouse design and management," ed: Taylor & Francis, 2017
- [2] F. Yener and H. R. Yazgan, "Optimal warehouse design: Literature review and case study application," *Computers & Industrial Engineering*, vol. 129, pp. 1-13, 2019/03/01/2019.
- [3] M. Schenone, G. Mangano, S. Grimaldi, A. C. J. P. Cagliano, and M. Research, "An approach for computing AS/R systems travel times in a class-based storage configuration," vol. 8, no. 1, pp. 273-290, 2020.
- [4] Y. Zhao, Y. Shi, and H. Karimi, "Entry-Item-Quantity-ABC Analysis-Based Multitype Cigarette Fast Sorting System," *Mathematical Problems in Engineering*, vol. 2012, 11/21 2012.
- [5] C.-K. Kao, G.-X. Xu, X.-E. Fang, and M.-C. Zheng, "Case Study of building Storage Strategy in the Logistics Distribution Center—Logistics Company A as an Example," *European Journal of Engineering Research and Science*, vol. 3, p. 40, 04/24 2018.
- [6] N. Setiawan, F. Setiawan, Y. Herawati, "Usulan Perbaikan Tata Letak Gudang Barang Jadi PT X Menggunakan Class-Based Storage Berdasarkan Analisis Entry Item Quantity (EIQ)", 2018.
- [7] U. Venkatadri and S. Kubasad, "Estimating Travel Distances and Optimizing Product Placement for Dedicated Warehouses with Manual Picking," 2012.







icimece 2021

This is to certify that

Warehouse Design under Class-Based Storage Policy Based on Entry-Item-Quantity Analysis: A Case Study

has been presented by

Sekarsari Utami Wijaya, Rahayu Johanna, Muhammad Faisal Ibrahim

In The 7th International Conference on Industrial, Mechanical, Electrical and Chemical Engineering (ICIMECE 2021)

Surakarta, Indonesia on October 5th, 2021



Indexed by:

Scopus'







Organized by:

